

# AGSORB<sup>®</sup>

## -325 RVM<sup>tan</sup> GA

### PRODUCT DESCRIPTION

This powder sized granule works well in wetttable powder formulations, as a seed treatment/coating, or in formulations requiring a flowable carrier. This RVM material can slake and become cloudy in liquid formulations.

### MINERAL DESCRIPTION

AGSORB<sup>®</sup> from Ochlocknee, Georgia is an Attapulgite mineral in the non-swelling bentonite class. It is commonly called Fuller's earth. Its low bulk density and high absorptivity allows higher liquid holding capacity. Our mineral processing maximizes the granule's micropore space. AGSORB<sup>®</sup> heat treatments impart a hard, inert granule with a high resistance to attrition.



OCHLOCKNEE,  
GEORGIA

### TYPICAL CHEMICAL ANALYSIS

Component	Weight % VOLATILE FREE BASIS
SiO <sub>2</sub> .....	70.81
Al <sub>2</sub> O <sub>3</sub> .....	14.12
CaO.....	2.22
MgO.....	4.57
Na <sub>2</sub> O.....	0.23
K <sub>2</sub> O.....	1.30
Fe <sub>2</sub> O <sub>3</sub> .....	4.98
MnO.....	0.04
P <sub>2</sub> O <sub>5</sub> .....	0.99
TiO <sub>2</sub> .....	0.62
FeO.....	0.11
Loss on Ignition.....	6.0